



HUSQVARNA GX 560

Husqvarna GX 560 provides all the benefits of air cushion mowing with the additional benefit of petrol power freedom. So easy and manoeuvrable, the GX 560 makes difficult outlying areas more accessible. Designed for large-scale domestic use the GX 560 features a powerful, high quality engine for use on slopes of up to 45°.



Cuts on slopes up to 45°

Cuts continuously on slopes up to 45° due to the oil throw engine lubrication system.



Manoeuvrable

Easy to move around obstacles in the landscape such as flower beds, trees and up to edges.

Air cushion

Floats on a cushion of air and cuts easily in any direction.



FEATURES

- Cuts easily in any direction through air cushion.
- Easy to move around in any directions.
- Cuts continuously on slopes up to 45°.

Technical Specifications	
CAPACITY	
Net power at preset rpm	3150 rpm
Power output	3.4 kW
DIMENSIONS	
Article gross weight	22000 g
Article net weight	18000 g
Cutting width	50.5 cm
Cylinder displacement	166 cm ³
Weight	18 kg
ENGINE	
Cylinder displacement	166 cm ³
Engine brand	Honda
Engine cooling	Air
Engine name	GCVX-170
Fuel tank volume	0.9 l
Motor/engine manufacturer	Honda
Motor/engine model	OHC
Spark plug	NGK BPR6ES
EQUIPMENT	
Blade brake clutch (BBC)	No
Blade type	Mulcher blade
Drive system	Push
Foldable handle	Yes
Handle type	Comfort
Lawnmower drive type	Hover mowers
Connectivity	Not applicable
LUBRICANTS	
Engine lubrication type	Splash
Power/fuel type	Petrol
MATERIAL	
Cutting deck material	ABS plastic
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
PACKAGING	
Packaging height	425 mm
Packaging length	765 mm
Packaging width	610 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	97 dB(A)
Sound power level, measured	96 dB(A)
Sound pressure level at operators ear	86 dB(A)
VIBRATION	
Vibrations handlebar	3.3 m/s ²